


SA300 CAD-CUT® Premium Plus Sublistop

100% Polyurethane

Roll Length: 25m x Roll Width: 0,5m

Stahls

CREAM 005 (CA. P. 479C)	GOLD 115 (CA. P. 871C)	GREY 730 (CA. P. 7543C)	LIGHT BLUE 320 (CA. P. 298C)	LIGHT GREEN 422 (CA. P. 362C)	LIGHT ORANGE 185 (CA. P. 1495C)	RED 200 (CA. P. 186C)	SILVER 815 (CA. P. 877C)	TURQUOISE 380 (CA. P. 7717C)
WHITE 001	YELLOW 110 (CA. P. 012C)							

Polyurethane (PU) flex film with sublimation barrier layer and optimal coverage | Adhesive carrier | Especially for the printing of functional clothing and softshell jackets | Easy cutting and weeding | Suitable for multicolour proofs | Temperature: 130°C, Time: 10 sec., Pressure: medium, (#4–6 on Hotronix®), Peel: cold | Recommended fabrics: 100% polyester, 100% sublimated polyester, polyester-cotton blends, polyester caps, polyester mesh | Multi-colour designs: Apply background for 3–5 sec. peel carrier cold, repeat process for each additional colour, apply last colour for 18–20 sec., peel carrier cold | You should always test cut prior to any production run, cutter settings will need to be adjusted as the blade ages | For optimal cutting and weeding, maintain a line thickness of at least 2.5 mm for lettering and logos | Washable up to 40 °C | Do not use fabric softeners or bleach | Suitable for drying with gentle adjustment | Can be directly ironed | Store in cool, dry area; avoid direct heat and sunlight