


SA910 CAD-CUT® Silicone 100

Roll Length: 25m x Roll Width: 0,5m

Stahls

BLACK 700	GREEN 400 (CA. P. 7727C)	GREY 730 (CA. P. 422C)	LIGHT BLUE 320 (CA. P. 2148C)	PASTEL BLUE 321 (CA. P. 538C)	PASTEL PINK 255 (CA. P. 700C)	PASTEL PURPLE 285 (CA. P. 2071C)	RED 200 (CA. P. 186C)	ROYAL BLUE 300 (CA. P. 286C)
TURQUOISE 380 (CA. P. 7717C)	WHITE 001							

0.1 mm thick silicone film with a matt surface and soft feel | The material is stretchable and prevents dye migration on sublimated polyester | Temperature: 150°C, Time: 10 sec., Pressure: medium, (#4–6 on Hotronix®), Peel: cold, Reprint: 5 sec. | Recommended fabrics: 100% cotton, 100% polyester (Test before application), Polyester-cotton blends, sublimated polyester | Multi-Colour-Designs: is not suitable for multi-layer application | You should always test cut prior to any production run, cutter settings will need to be adjusted as the blade ages | For optimal cutting and weeding, maintain a line thickness of at least 1.0 mm for lettering and logos | Washable up to 60°C | Do not use fabric softeners or bleach | Suitable for drying with gentle adjustment | Washing and ironing inside out | Store in cool, dry area; avoid direct heat and sunlight