

**PT300** | 854**Poli-Tack 854**

100% Polyester

Roll Length: 25m x Roll Width: 0,5m

Poli-Tack

STANDARD

Technical data- Carrier: PET film, transparent/Adhesive: acrylate/ Adhesive strength [N/cm]: 0.60 +/- 10%/Thickness [mm]: 0.12 +/- 10%/Lining: PP film, white, siliconised. | Transparent PET film coated with a cross-linked acrylic adhesive offering excellent temperature resistance, ageing and UV stability. | The adhesive can be removed without residue even after long periods of usage. | Suitable for use as a transfer film for heat transfer printing with heat-sealable materials, such as printing designs on flex films onto textiles.

**PT301** | 870**Poli-Tack 870 Universal**

100% Polyester

Roll Length: 25m x Roll Width: 0,5m

Poli-Tack

STANDARD

Technical data- Carrier: PET film, transparent/Adhesive: acrylate/ Adhesive strength [N/cm]: 0.50 +/- 10%/Thickness [mm]: 0.12 +/- 5%/Lining: PP film, white, siliconised. | Transparent PET film coated with a cross-linked acrylic adhesive offering excellent temperature resistance, ageing and UV stability. | The adhesive can be removed without residue even after long periods of usage. | Suitable for use as a transfer film for heat transfer printing with heat-sealable materials, such as printing designs on flex films onto textiles.