


**SA903 CAD-CUT® Basic Film**

Roll Length: 25m x Roll Width: 0,5m

Stahls

BLACK 700	GOLD 115 (CA. P. 871C)	GREEN 400 (CA. P. 7727C)	NAVY 350 (CA. P. 532C)	RED 200 (CA. P. 186C)	ROYAL BLUE 300 (CA. P. 286C)	SILVER 815 (CA. P. 877C)	WHITE 001	YELLOW 110 (CA. P. 012C)
-----------	------------------------	--------------------------	------------------------	-----------------------	------------------------------	--------------------------	-----------	--------------------------

Polyurethane (PU) flex film with matt surface and optimum coverage | Ideal for plotting larger motifs and numbers, as the material has a non-adhesive backing | Suitable for multicolour proofs | Temperature: 160°C, Time: 10 sec., Pressure: medium, (#4–6 on Hotronix®), Peel: cold | Recommended fabrics: 100% cotton, 100% polyester (Test before application), polyester-cotton blends | Multi-colour designs: Apply background for 3–5 sec. peel carrier cold, repeat process for each additional colour, apply last colour for 18–20 sec., peel carrier cold | You should always test cut prior to any production run, cutter settings will need to be adjusted as the blade ages | For optimal cutting and weeding, maintain a line thickness of at least 1.5 mm for lettering and logos | Washable up to 60°C | Do not use fabric softeners or bleach | Suitable for drying with gentle adjustment | Washing and ironing inside out | Store in cool, dry area; avoid direct heat and sunlight