



SA350 CAD-CUT® Flock

Roll Length: 25m x Roll Width: 0,5m

Stahls

AQUA 390 (CA. P. 3125C)	BERRY 253 (CA. P. 2046C)	BLACK 700	BROWN 530 (CA. P. 4695C)	BURGUNDY 270 (CA. P. 505C)	COOL GREY 730 (CA. P. COOL GRAY 6C)	DARK BROWN 550 (CA. P. 7617C)	DARK GREY 780 (CA. P. 432C)	GREEN 400 (CA. P. 7733C)
ICE BLUE 310 (CA. P. 297C)	LEMON 100 (CA. P. YELLOW 012C)	LIME GREEN 405 (CA. P. 367C)	MAGENTA 245 (CA. P. 214C)	MINT 419 (CA. P. 7471C)	NAVY 350 (CA. P. 534C)	NEON GREEN 401	NEON ORANGE 181	NEON PINK 241
NEON YELLOW 101	ORANGE 180 (CA. P. 021C)	PASTEL PINK 255 (CA. P. 700C)	PURPLE 280 (CA. P. 7665C)	RED 200 (CA. P. 1935C)	ROYAL BLUE 300 (CA. P. 2370C)	SIGNAL RED 210 (CA. P. 199C)	SKY BLUE (CA. P. 2131C)	WHITE 001
YELLOW 110 (CA. P. 2010C)								

Due to the long and dense flock fibres, this film has high opacity, colour brilliance and a soft, velvety feel | Equipped with an adhesive backing, even fine details can be easily cut and weeded | Temperature: 165°C, Time: 15 sec., Pressure: medium (#4–6 on Hotronix®), Peel: warm/cold | Recommended fabrics: 100% cotton, 100% polyester (Test before application), polyester-cotton blends | Multi-colour designs: Not suitable for multi-layer application | You should always test cut prior to any production run, cutter settings will need to be adjusted as the blade ages | For optimal cutting and weeding, maintain a line thickness of at least 1.5 mm for lettering and logos | Washable up to 60°C | Do not use fabric softeners or bleach | Suitable for drying with gentle adjustment | Can be directly ironed | Store in cool, dry area; avoid direct heat and sunlight