



## SA100 CAD-CUT® Premium Plus

100% Polyurethane

Roll Length: 25m x Roll Width: 0.5m

Stahls

APPLE GREEN 421 (CA. P. 368C)	AQUA 360 (CA. P. 631C)	BEIGE 004 (CA. P. 4685C)	BERRY 253 (CA. P. 225C)	BLACK 700	BROWN 550 (CA. P. 7616C)	BURGUNDY 270 (CA. P. 188C)	COLUMBIA 330 (CA. P. 4150C)	CREAM 005 (CA. P. 479C)
DARK GREEN 410 (CA. P. 560C)	DARK GREY 780 (CA. P. 419C)	DEEP NAVY 335 (CA. P. 2378C)	DOVE BLUE 340	FUCHSIA 250 (CA. P. 214C)	GOLD 115 (CA. P. 871C)	GREEN 400 (CA. P. 7727C)	GREY 730 (CA. P. 7543C)	ICEBERG GREEN 424 (CA. P. 443C)
LEMON 100 (CA. P. 7405C)	LIGHT BLUE 320 (CA. P. 298C)	LIGHT GREEN 422 (CA. P. 362C)	LIGHT ORANGE 185 (CA. P. 1495C)	MEDIUM BROWN 555 (CA. P. 2472C)	MID GREY 740 (CA. P. COOL GRAY 10C)	MINT 419 (CA. P. 339C)	NAVY 350 (CA. P. 532C)	NEON BLUE 301
NEON GREEN 401	NEON ORANGE 181	NEON PINK 241	NEON YELLOW 101	OLIVE 430 (CA. P. 7763C)	ORANGE 180 (CA. P. 021C)	PASTEL BLUE 321 (CA. P. 538C)	PASTEL GREEN 420 (CA. P. 358C)	PASTEL MINT 370 (CA. P. 317C)
PASTEL PINK 255 (CA. P. 2036C)	PASTEL PURPLE 205 (CA. P. 2071C)	PASTEL YELLOW 105 (CA. P. 602C)	PEACH 006 (CA. P. 712C)	PINK 252 (CA. P. 507C)	PISTACHIO GREEN 425 (CA. P. 5777 C)	PURPLE 280 (CA. P. 2096C)	RED 200 (CA. P. 186C)	ROSE PINK 256 (CA. P. 694 C)
ROSÉ GOLD 215	ROYAL BLUE 300 (CA. P. 286C)	SAGE GREEN 423 (CA. P. 7537C)	SAHARA YELLOW 104 (CA. P. 7407 C)	SIGNAL RED 210 (CA. P. 185C)	SILVER 815 (CA. P. 877C)	SUNFLOWER YELLOW 106 (CA. P. 137C)	TEXAS ORANGE 182 (CA. P. 4013C)	TURQUOISE 380 (CA. P. 7717C)
VINTAGE PINK 254	WHITE 001	YELLOW 110 (CA. P. 012C)						

Polyurethane (PU) flex film, high coverage and a matt surface finish | Soft hand feel | Adhesive carrier | Easy cutting and weeding | Applicable to almost all common types of textiles | Suitable for multi-colour proofs | Cotton, cotton blend, elastane etc.: Temperature: 130°C/150°C, Time: 10 sec. / 5 sec. Pressure: Medium (#4–6 on Hotronix®), Peel: hot | On nylon/nylon-blend: Temperature: 130°C, Time: 10 sec., Pressure: Light, (#2–4 on Hotronix®), Peel: Light | Recommended fabrics: 100% cotton, 100% polyester (Test before application), 100% nylon (Please consider the other application instruction), Polyester-cotton-blends, Elastane, Satin, Polyester mesh | Multi-colour designs: Apply background for 3–5 sec. peel carrier cold, repeat process for each additional colour, apply last colour for 18–20 sec., peel carrier cold | You should always test cut prior to any production run, cutter settings will need to be adjusted as the blade ages | For optimal cutting and weeding, maintain a line thickness of at least 2.0 mm for lettering and logos | Washable up to 60°C, up to 30°C on nylon fabric | Do not use fabric softeners or bleach | Suitable for drying with gentle adjustment | Can be directly ironed | Store in cool, dry area; avoid direct heat and sunlight